

Care instructions for ORALITE® 5600E Fleet Marking Grade

Care & Maintenance

It is not recommended to use high-pressure cleaning, aggressive chemicals or solvents (such as acetone, paint thinner, tar remover) as this will reduce the service life of the film. The following practices will help maintain the life and quality of the reflective film:

ORAFOL recommends regular cleaning and maintenance of the vehicle by hand.

If using a cleaning product, wash applied film with a blend of clean water and a mild car wash detergent.

Test any cleaning solution on a small section of the film before using. Always read the warning labels on car care products for proper safety instructions.

Once you've washed the vehicle with the soapy water blend, rinse it with clean water.

Either let the vehicle air dry or use a microfiber cloth.

Please obey the following instructions, otherwise it may result e.g. in a loss of gloss level, fading, embrittling and cracking, chipping, or peeling around edges:

Do not allow fuels to stay in contact with the film for extended periods of time. Clean all spills as soon as possible.

Do not use automated car washes, truck washes using caustic cleaners, tar remover, or pressure washers to clean your vehicle

Do not apply any type of wax or polish over the material.

Do not use mechanical brush washing.

In case of any doubt, please contact our Customer Support.

The instructions are solely based on information provided by the manufacturer. Therefore, we assume no liability for the correctness of the content.